### Public Hearing

# "Reducing C02 from passenger cars and light-commercial vehicles"

# ETRMA response: Tyre performances integrated proposal




F. Cinaralp, July 11 2007

### The ETRMA tyre industry members

- 10 tyre companies;
- 240 million of tyres produced per year (2<sup>nd</sup> after China)
- 200 000 direct jobs
- up to 3.8% of annual TU is invested in R&D each year
- ETRMA members realise 72% of worldwide turnover;
   37% is realised in Europe




### Tyre rolling resistance



The same way a rubber ball does not rebound as high as it was launched, energy is dissipated when a tyre rolls and is deformed.

This phenomenon is called Rolling Resistance (RR). It contributes, together with vehicle's other sources of drag, to its fuel consumption and, thus, to its CO2 emissions.

## RR has an influence on CO<sub>2</sub> (and other) emissions by transport



RR is usually expressed in kg/t (drag in kg per ton of load on the tyres).

# Tyre rolling resistance and its influence on vehicle consumption and C02 emissions

- The rolling resistance of tyres is in itself a key factor in determining vehicle fuel consumption;
- Depending on the type of road and driving style, rolling resistance causes about 20% of the CO2 emitted by a car, and about 30% of the CO2 emitted by a heavy truck.

#### Two technological solutions are identified:

Measure	Expected C02 emissions reduction
Tyre pressure maintenance permanently kept at placard level	1-2.5%
Both safety and environmental benefits!	
Low Rolling Resistance tyres	3-4%

Source: Tyre Industry, Cars21

The correct tyre inflation pressure is essential for delivering the tyre performance and all efforts must be made to guarantee proper setting and maintenance of the inflation pressure

**Inflation pressure** has an unquestionable influence on tyre rolling resistance. Since under-inflation increases rolling resistance, it has a direct effect on both vehicle fuel efficiency and emissions.

With a permanent 20 to 25% under-inflation, the tyre rolling resistance is increased by 10%, which in turn results in about 2% more fuel consumption.

The lower the tyre inflation pressure, the higher the effect on rolling resistance!

### **Tyre Performances**

The "to-be" regulated performance items are not independent from each other and imposing too high constraints on a single property only, will have a negative impact on other properties



There is a relationship between Rolling Resistance and Wet Grip performances

# Summary of tyre industry proposal and expected C02 emissions reduction

Introduce an <u>integrated regulatory framework</u> covering the key tyre performances criteria:

- Establish maximum limits and a Grading for RR to assure that consumers can make informed choices
  - **❖** quantitative potential of ~ 22 Mt.CO2 annual savings
- Maintenance of inflation pressure at placard value; which foresees a.o. compulsory fitment of <u>accurate</u> tyre pressure monitoring systems
  - **❖** quantitative potential of ~10 Mt.CO2 annual savings
- Observe minimum limits and a Grading for Wet Grip to make sure that low RR tyres are achieved without compromising safety

Implement appropriate controls to establish fair global competition within the EU market



Thank you!